

Original post set 1821 by William B. Laughlin with witnesses: 12" beech N 80 E 17 links, 10" beech S 70 W 12 links per Marion County Atlas pg. 16. Survey, 3-1854 by Wilson per Lawrence Township Legal Survey Book pg. 14 labels the corner "N" and calls it a rock. Distances are given to corner on the N and E. Legal survey 10-1866 by William Smith per Lawrence Township Legal survey Book pg. 13 gives distances to corners to the W but no information on the corner itself. Legal Survey 8-1884 by Fatout per Lawrence Township Legal Survey Book pg. 13 also gives distances to corners on the W. The survey also notes that both original witnesses were standing. Legal Survey 6-1884 by Fatout per Lawrence Township Legal Survey Book pg. 39 labels the corner "9" but gives no information except distances to corners to the S. Two, undated, tie cards show exactly the same references and distances to the corner, which is not identified by type of marker. 5-22-79 Wilcoxen called stone. Ties converted to typed copy 3-12-82. Excavated 8-13-82 and stone at surface was removed and Harrison set. Top of monument is 6" above grade due to a large root 24" inches down. Re-tied 6-24-99 by Kiste.

## HC753301

REF.	DISTANCE	DESCRIPTION	
1.	13.00′	Face of steel chain link joint post (6' chain link	fence)
2.	5.64'	Boat spike N 36' cherry 48'up	
3.	11.20′	PK nail w/MCSO washer N 8" ash 48"up	
4.	23.00′	Face of steel (end) post	